



FINZZI
SURFACES

Solid

LUXURY VINYL TILES

2 COLORS
6 SIZES

Solid
Black & White
18"x36" & 36"x36" /
46x91 cm & 91x91cm

Solid

Monochrome smooth pieces without streaks that infuse seriousness into the spaces.

Sizes



12" x 48" / 30 x 123cm



36" x 36" / 91 x 91cm



18" x 36" / 46 x 91cm



12" x 36" / 30 x 91cm



12" x 24" / 30 x 61cm



18" x 18" /
46 x 46cm

Colors



Product Typology



LVT Glue
Down



SPC Click

Configuration



Real Touch®



Drop'n'Click®



IXPE pad



Wear Layer

FINZZI

Solid White & black



Solid
Black & White
18"x36" & 36"x36" /
46x91 cm & 91x91cm

Product Advantages



Real Touch®
True to nature.
Real Touch®
Fiel a la naturaleza.



Drop'n' Click®
The perfect union.
Drop'n' Click®
La unión perfecta.



Cost effective
Overall cheaper to buy and install than conventional tile.
Económico
En general más barato de comprar e instalar que los azulejos convencionales.



Phthalate free technology
We use alternative plasticizers with substance-free technologies.
Tecnología libre de Ftalatos
Utilizamos plastificantes alternativos con tecnologías libres de sustancias nocivas.



Floor Score certified
All our products are Floor Score certified.
Certificado Floor Score
Todos nuestros productos tienen el certificado Floor Score.



Dust free build
No build debris.
Construcción libre de polvo
Sin restos de construcción.



Stain resistant & low maintenance
The top layer protects against knock and stains, they can be removed in seconds.
Resistente a las manchas y bajo mantenimiento
La capa superior protege contra golpes y manchas, pudiendo eliminarlos en segundos.



Waterproof
Moisture-resistance, ideal in kitchen or bathrooms.
Resistente al agua
Resistencia a la humedad, ideal en cocina o baños.



Floor & wall use
All our products can be applied to any surface, either floor or wall.
Uso para suelo y pared
Todos nuestros productos se pueden aplicar a cualquier superficie ya sea suelo o pared.



IXPE pad
Moisture barrier and sound proofing.
Pad IXPE
Barreda de humedad e insonorización.



Suitable for underfloor heating
Finzzi's floors are perfectly compatible with underfloor heating.
Preparado para suelo radiante
Los suelos de Finzzi son perfectamente compatibles con calefacción por suelo radiante.



Antislip
Firm under foot, with a slip resistance value of R10.
Antideslizante
Con un valor de resistencia al deslizamiento de R10.



High impact resistance
Does not leave traces or marks when supporting strong blows.
Alta resistencia al impacto
No deja huellas ni marcas al soportar golpes fuertes.



Wear Layer
Commercial grade wear layer protection.
Capa de protección
Capa de desgaste protectora para uso comercial.

PROFILING INFO



Flush stair nose A
2400x72x25mm
 Escalón empotrado A
 2400x72x25mm



Flush stair nose B
2400x115x25mm
 Escalón empotrado B
 2400x115x25mm



Skirting 90mm
2400x90x15mm
 Rodapié 90mm
 2400x90x15mm



Skirting 80mm
2400x80x15mm
 Rodapié 80mm
 2400x80x15mm



Stair nose
2400x58x18mm
 Peldaño
 2400x58x18mm



Reducer
2400x43x10mm
 Reductor
 2400x43x10mm



End-Cap
2400x35x7mm
 Tapa de acabado
 2400x35x7mm



T-molding
2400x46x7mm
 Moldura en forma de T
 2400x46x7mm



Quarter round
2400x28x16mm
 Cuarto de circunferencia
 2400x28x16mm

| Profiling | Flooring Thickness | Pcs/box | Kg/box |
|----------------------------------|--------------------|---------|--------|
| T-moulding 2400x46x7mm | 4~8mm | 20 | 10 |
| Reducer 2400x43x10mm | 4~8mm | 20 | 15 |
| End-Cap 2400x35x7mm | 4~8mm | 20 | 14 |
| Stair Nose 2400x54x18mm | 4~8mm | 10 | 11 |
| Flush Stair Nose A 2400x72x25mm | 4~8mm | 10 | 15 |
| Flush Stair Nose B 2400x115x25mm | 4~8mm | 10 | 18 |
| Quarter Round 2400x28x16mm | 4~8mm | 25 | 17 |
| Skirting 2400x90x15mm | 4~8mm | 10 | 20 |
| Skirting 2400x80x15mm | 4~8mm | 10 | 11 |

NOTE: The thickness of the profiling might vary slightly according to the thickness of the flooring

NOTA: El espesor del perfil puede variar ligeramente de acuerdo con el espesor del suelo.

TECHNICAL INFORMATION

| TECHNICAL PERFORMANCES | TEST STANDARDS | SOLID |
|-------------------------|------------------------------|---|
| Dimensional stability | ASTM F2199 - 09(2014) | MD MAX = -0.11mm / 185mm - PASS CMD MAX = -0.10mm / 164mm - PASS |
| Impact resistance | ASTM F1265 - 03a(2013) | No crack or breakage |
| Reaction to fire | EN 13501 - 1 | Bfl s1 on concrete and Cfl s1 on wood substrate |
| Residual indentation | ASTM F1914 - 07 (2011) | 1.3% max |
| Castor chair | NALFA LF 01-2011 Section 3.9 | No damage visible after 25000 revolutions |
| Underfloor heating | EN ISO 10456 | Suitable - max. 27°C / 81°F |
| Thermal resistance | ISO 10456 | 0.04 m ² K/W |
| Impact sound insulation | ASTM E492-09 | IIC = 64 |
| Resistance to light | ASTM F1515-15 | ≥8 (2.14) PASS |
| Resistance to chemicals | ASTM F925-13 | High resistance |
| Slip resistance | DIN 51130-2014 | Angle 23.5° - R10 |
| Swelling in thickness | ASTM D7519-11 | AVE: -0.30% |
| Fungi resistance | ASTM G21-15 | No traces |
| Formaldehyde content | ASTM D6007-14 | Not detected |
| Resistance to heat | ASTM F1514-03(2013) | After 7 days exposure: ΔE* = 0.30 |
| Smoke density | ASTM E662 | Less than 450 |
| Indoor air quality | Floor Score Certified | |
| Heavy metal detection | ASTM F963-16 | Not detected |
| Phthalate content | CPSC - CH - C1001 - 09.3 | Not detected |
| Coefficient of friction | ASTM C1028-07 | Dry condition average: 0.87 Wet condition average: 0.70 |



FINZZI
SURFACES

Finzzi Corporate Offices

Calle La Cosa 57, 12200 Onda (Castellón), Spain

Finzzi Sales USA

225 Executive Drive, Suite 8, Moorestown, New Jersey 08057

Email address

info@finzzi.com

Email address

finzzi@finzziusa.com


Website

www.finzziusa.com

Follow us

 [#finzzisurfaces](#)

 [#finzzisurfaces/](#)

 [#finzzi-surfaces/](#)